

KZ-1860-CL

Highly Accurate ABS Like Resin

Solid State
355 nm Lasers

Description:

Allied PhotoPolymers KZ-1860-CL is a tough ABS like, dimensionally stable resin for 355 nm Solid State Laser Systems. It is ideal for quickcast applications as well as general purpose and dimensionally challenging builds. Superior humidity resistance and exceptional shrink characteristics are major differentiators.

Applications:

Prototype Tooling
Quickcast
Small Feature Connectors
RTV Patterns
Concept Models
Medical Applications


Characteristics:

- ✓ Quality finishing
- ✓ Fast building
- ✓ Low viscosity
- ✓ Water resistant
- ✓ Superb green strength
- ✓ Excellent re-wetting
- ✓ Supports break clean
- ✓ Clear w/ slight green tint
- ✓ Excellent viscosity stability
- ✓ Superior dimensional stability over time
- ✓ Terrific thermal stability over time
- ✓ Passed ISO 10993 Bio-Compatibility / Toxicity Testing



Owned and
Manufactured
In USA

PHYSICAL PROPERTIES		
DESCRIPTION	UNITS	VALUE
Viscosity	Cps	270
Appearance	Clear / green tint	na
Critical Exposure (Ec)	mj/cm ²	11.2
Penetration Depth (Dp)	mils	6.6
Liquid Density	g/cm ³	1.12



MECHANICAL PROPERTIES			
MEASUREMENT	ASTM METHOD	UNITS	VALUE
Tensile Strength	ASTM D638	MPa ksi	52 7.54
Tensile Modulus	ASTM D638	MPa ksi	2500 363
Elongation at Break	ASTM D638	%	6 to 10
Flexural Strength	ASTM D790	MPa ksi	82 11.9
Flexural Modulus	ASTM D790	MPa ksi	2000 290
Impact Strength Notched Izod	ASTM D256	J/m ft-Lb/in	21.4 0.4
Hardness	ASTM D2240	Shore D	83
Heat Deflection 264 psi	ASTM D648	°C °F	50 122
Heat Deflection 66 psi	ASTM D648	°C °F	55 131
Water Absorption	ASTM D570-98	% weight	0.23

